



Thank you for purchasing a Scaggs Moto Designs Billet Adventure rack  
for your Honda Africa Twin 1100

Mounting is Easy!

1. Locate the 4 Aluminum spacers from the bolts package and place on the OEM Tail Rack in the counterbores.
2. Place the new ADV rack on top of the spacers with the 4 M8x45mm Flat Head screws.
3. Once the holes are aligned, drop the screws through and place a washer and nut on each screw on the underneath side of the rack.
4. Tighten all the nuts, not too tight, they are nylon inserted locknuts and do not need excessive torque.

This rack is ready for the installation of a Rotopax Pack mount and or Givi Monokey top case mounting kit

#### GIVI PART# E115F Junction Kit.

To mount the Givi Monokey top case mounting kit, place the pyramid block over the two rear most  $\frac{1}{4}$ " holes 1" apart and attach using supplied screws with the notch facing the front of the bike. Bolt the 2 Mushroom lugs to the front two  $\frac{1}{4}$ " holes approximately 9" apart.

If purchased with your rack you will receive also two M6x60 mm screws to mount a Rotopax pack mount directly to the top of the rack. Remember the retaining threads are in aluminum, so don't over torque the bolts, or install with an impact wrench. Check and re-tighten as needed. The round universal flange that comes with the pack mount will not be used in this application.

For answers to any questions about your Scaggs Moto Designs products or installation please email [Jared@scaggsmotodesigns.com](mailto:Jared@scaggsmotodesigns.com)